















## FAN COILS

		kW
FCA		1,5 - 11,3
		3,4 - 24,2
CA		2,6 - 11,3
		5,8 - 22,9
FM		2,1 - 4,6
		4,8 - 7,7
FA		1,6 - 11,3
		3,4 - 24,2
FEP		7,2 - 23,6
		14,8 - 47,1
KTR		9,5 - 63,2
		9,5 - 63,2
KTM		6,4 - 39,6
		4,6 - 90,8

### LEYENDA / KEY / LÉGENDE

	frío / cold / froid
	calor / hot / chaud
V	Vertical
H	Horizontal / Horizontel
2T	2 tubos / 2 pipes / 2 tuyeaux
4 T	4 tubos / 4 pipes / 4 tuyeaux
KIT V3V+ACTUADOR	KIT V3V + actuator / agitateur
TM ICR11 (On/Off+ 3V + I/V + T/N)	3V: 3 velocidades / 3 speed / 3 vitesses I/V: invierno/verano // winter/summer // hiver/été T/N: todo/nada // on/off // tout/rien)

**SERIE FAC. FAN COIL CARROZADO TIPO CONSOLA-TECHO**  
 FAC SERIES. BODIED FAN COIL ROOF-CABINET TYPE · SÉRIE FAC. FAN COIL CARROSSÉ TYPE CONSOLE-TOIT

FAC: vertical 2T-4T  
 FACH: horizontal 2T



**CARACTERÍSTICAS CONSTRUCTIVAS**

La serie FAC son ventilosconvectores tipo consolas compactas con un espesor de 220 mm, para su instalación en pequeños espacios interiores.

**CONSTRUCTION CHARACTERISTICS**

FAC series are compact cabinet type fan convectors with 220 mm thickness, to be installed in little inner areas.

**CARACTERISTIQUES CONSTRUCTIVES**

La série FAC sont ventilosconvecteurs type console avec un épaisseur de 220 mm, pour l'installer au petits espaces.

FAC 2T MODEL	12	22	32	42	52	62	72	82	92	102	112	122
<b>REFRIGERACIÓN / COOLING / RAFRAÎCHISSEMENT</b>												
Capacidad frigorífica total (7/12°C y 27°C 50%HR)	1,6	2,1	2,7	3,2	3,9	4,5	5,8	6,8	7,9	9,5	10,1	11,3
<b>CALEFACCIÓN / HEATING / CHAUFFAGE</b>												
Potencia calorífica (kW) (20°C-70/60°C)	3,4	4,3	5,5	6,1	8	9,2	12,2	13,6	17	19,1	21,1	24,2
<b>DATOS GENERALES / GENERAL DATA / DONNÉES GÉNÉRALES</b>												
Caudal aire (m³/h)	350	360	435	447	647	665	975	1.003	1.431	1.472	1.908	1.962
<b>DIMENSIONES / MEASURES / MESURES</b>												
Largo (A)	mm	670	670	870	870	1.070	1.070	1.270	1.270	1.470	1.470	1.670
Alto (B)	mm	220	220	220	220	220	220	220	220	220	220	220
Ancho (C)	mm	470	470	470	470	470	470	470	470	470	470	470
Peso	Kg	13	14	16	17	22	23	26	27	30	31	37

FAC 4T MODEL	14	34	54	74	94	114
<b>REFRIGERACIÓN / COOLING / RAFRAÎCHISSEMENT</b>						
Capacidad frigorífica total (7/12°C y 27°C 50%HR)	1,6	2,7	4,0	6,0	8,1	10,4
<b>CALEFACCIÓN / HEATING / CHAUFFAGE</b>						
Potencia calorífica (kW) (20°C-70/60°C)	1,8	3,0	4,3	9,1	14,7	10,3
<b>DATOS GENERALES / GENERAL DATA / DONNÉES GÉNÉRALES</b>						
Caudal aire (m³/h)	360	447	665	625	1.145	1.962
<b>DIMENSIONES / MEASURES / MESURES</b>						
Largo (A)	mm	670	870	1.070	1.270	1.470
Alto (B)	mm	220	220	220	220	220
Ancho (C)	mm	470	470	470	470	470
Peso	Kg	14	17	24	28	38