















FAN COILS

| | | kW |
|-----|---|-------------|
| FCA |  | 1,5 - 11,3 |
| |  | 3,4 - 24,2 |
| CA |  | 2,6 - 11,3 |
| |  | 5,8 - 22,9 |
| FM |  | 2,1 - 4,6 |
| |  | 4,8 - 7,7 |
| FA |  | 1,6 - 11,3 |
| |  | 3,4 - 24,2 |
| FEP |  | 7,2 - 23,6 |
| |  | 14,8 - 47,1 |
| KTR |  | 9,5 - 63,2 |
| |  | 9,5 - 63,2 |
| KTM |  | 6,4 - 39,6 |
| |  | 4,6 - 90,8 |

LEYENDA / KEY / LÉGENDE

| | |
|---|---|
|  | frío / cold / froid |
|  | calor / hot / chaud |
| V | Vertical |
| H | Horizontal / Horizontel |
| 2T | 2 tubos / 2 pipes / 2 tuyeaux |
| 4 T | 4 tubos / 4 pipes / 4 tuyeaux |
| KIT V3V+ACTUADOR | KIT V3V + actuator / agitateur |
| TM ICR11 (On/Off+ 3V + I/V + T/N) | 3V: 3 velocidades / 3 speed / 3 vitesses I/V: invierno/verano // winter/summer // hiver/été T/N: todo/nada // on/off // tout/rien |

SERIE CA. FAN COIL CASSETTE PARA INSTALACIÓN EN FALSO TECHO
 CA SERIES. CASSETTE FAN COIL FOR INSTALLATION ON FALSE CEILING
 CA SÉRIE. FAN COIL CASSETTE POUR INSTALLATION EN FAUX TOIT

CA 2T: Cassette 2 T
 CA 4T: Cassette 4 T



CARACTERÍSTICAS CONSTRUCTIVAS

La serie CA son ventilosconvectores tipo cassette para su integración en los falsos techos.

CONSTRUCTION CHARACTERISTICS

CA series are cassette type fan convectors to be installed on false ceilings.

CARACTERISTIQUES CONSTRUCTIVES

La série CA sont ventilosconvecteurs type cassette pour son integration en faux toits.

| CA 2T MODEL | | 22 | 42 | 62 | 82 | 122 | 142 |
|---|----|-----|-----|------|------|-------|-------|
| REFRIGERACIÓN / COOLING / RAFRAÎCHISSEMENT | | | | | | | |
| Capacidad frigorífica total (7/12°C y 27°C 50%HR) | | 2,6 | 4,5 | 5,6 | 6,2 | 8,6 | 11,26 |
| CALEFACCIÓN / HEATING / CHAUFFAGE | | | | | | | |
| Potencia calorífica (kW) (20°C-70/60°C) | | 5,8 | 9,2 | 10,7 | 12,0 | 17,5 | 22,96 |
| DATOS GENERALES / GENERAL DATA / DONNÉES GÉNÉRALES | | | | | | | |
| Caudal aire (m³/h) | | 660 | 680 | 770 | 890 | 1.280 | 1.570 |
| DIMENSIONES / MEASURES / MESURES | | | | | | | |
| Largo (A) | mm | 575 | 575 | 575 | 575 | 575 | 575 |
| Alto (B) | mm | 575 | 575 | 575 | 575 | 1.175 | 1.175 |
| Ancho (C) | mm | 255 | 255 | 255 | 255 | 255 | 255 |
| Peso | Kg | 22 | 23 | 23 | 23 | 44 | 46 |

| CA 4T MODEL | | 14 | 34 | 54 | 114 | 134 |
|---|----|-----|-----|-------|-------|-------|
| REFRIGERACIÓN / COOLING / RAFRAÎCHISSEMENT | | | | | | |
| Capacidad frigorífica total (7/12°C y 27°C 50%HR) | | 3,2 | 4,5 | 4,9 | 6,9 | 7,9 |
| CALEFACCIÓN / HEATING / CHAUFFAGE | | | | | | |
| Potencia calorífica (kW) (20°C-70/60°C) | | 3,6 | 5,3 | 5,8 | 7,7 | 10,4 |
| DATOS GENERALES / GENERAL DATA / DONNÉES GÉNÉRALES | | | | | | |
| Caudal aire (m³/h) | | 570 | 865 | 1.000 | 1.280 | 1.570 |
| DIMENSIONES / MEASURES / MESURES | | | | | | |
| Largo (A) | mm | 575 | 575 | 575 | 575 | 1.670 |
| Alto (B) | mm | 575 | 575 | 1.175 | 1.175 | 220 |
| Ancho (C) | mm | 255 | 255 | 255 | 255 | 470 |
| Peso | Kg | 23 | 24 | 47 | 47 | 38 |